



Rubber Conveyor Belts - Standardprogram

Strength	Cover mm	Thickness approx. mm	Weight approx. kg/m ²	Belt width in mm				
				500	650	800	1.000	1.200
EP 250/2	3+1,5	7,0	8,0	x	x	x		
EP 250/2	4+2	8,0	9,8	x	x	x		
EP 315/2	4+2	8,0	10,0	x	x	x		
EP 400/3	3+1	7,0	8,2	x	x	x	x	
EP 400/3	4+2	9,0	10,4	x	x	x	x	x
EP 400/3	5+2	10,0	11,1		x	x	x	
EP 400/3	6+2	11,0	12,8		x	x	x	
EP 500/3	4+2	9,0	10,9			x	x	
EP 500/3	5+2	10,0	12,1			x	x	
EP 500/3	6+2	11,0	13,3			x	x	
EP 500/4	4+2	10,0	11,6		x	x		
EP 500/4	5+2	11,0	12,8		x	x	x	x
EP 500/4	6+2	12,0	13,9			x	x	x
EP 630/3	6+2	12,0	14,3			x	x	x
EP 630/4	5+2	11,0	13,0			x	x	
EP 630/4	6+2	12,0	14,1			x	x	x
EP 630/4	8+3	15,0	17,7				x	x

Information:

the mentioned values are approx. and based on Y-grade solid or cut edges

Following cover grades are available (extract):

- Y** wear resistant cover for standard application
- X** wear resistant, heavy duty cover for sharp and lumpy material (or extreme drop heights)
- T** heat resistant cover grade (3 different grades)
- TC** chemical resistant grade
- G** oil- and fat resistant grade
- K** flame-resistant cover grade
- S** flame-resistant cover and carcass
- ...** a lot of other cover grades - **please contact us !**